





## 微型保险丝(延时型)

### Micro Fuse (Time-Lag) 250V



**测试标准:**  
**Testing Standard:**  
 IEC60127-1 IEC60127-3 GB/T9364.1 GB/T9364.3

**额定分断能力:**  
**Interrupting Rating:**  
 35A or 10In Whichever is greater


**工作温度:**  
**Operating Temperature:**  
 -55°C ~ +125°C

**材料:**  
**Materials:**  
 Case: thermoplastic nylon  
 Base: thermoplastic nylon  
 Lead wire: tinned copper wire

**焊接方法:**  
**Soldering Method:**  
 Wave soldering: 260°C, 10s max  
 Manual soldering: 370°C, 5s max

**包装:**  
**Packing:**  
 Automaton taped 1000 PCS per inner box,  
 10 inner boxes per external carton.







**Time-Current Characteristics**  
**电流-时间曲线图**



### 电气特性: Electrical Characteristics

额定电流的% % of Ampere Rating	熔断时间 Opening Time
210%	2 min Max(小于2分钟)
275%	400 ms~10 s
400%	150 ms~3 s
1000%	20 ms~150 ms

目录编号: Catalog No.A:250V.

目录编号 Catalog No.	额定电流 Ampere Rating	额定电压 Voltage Rating	最大电压降(mv) Max Voltage Drop	熔化热能 <sup>2</sup> T Melting Integral (A <sup>2</sup> .S)	认证 Approvals					
										
SRT0250A	250mA	250V	240	0.2	●	●		●		●
SRT0315A	315mA	250V	220	0.3	●	●		●		●
SRT0400A	400mA	250V	200	0.5	●	●		●		●
SRT0500A	500mA	250V	190	0.9	●	●		●		●
SRT0630A	630mA	250V	180	1.2	●	●		●		●
SRT0800A	800mA	250V	160	3.9	●	●		●		●
SRT1100A	1A	250V	140	5.8	●	●		●	●	●
SRT1125A	1.25A	250V	130	12.8	●	●		●	●	●
SRT1160A	1.6A	250V	120	14.7	●	●		●	●	●
SRT1200A	2A	250V	100	36.0	●	●		●	●	●
SRT1250A	2.5A	250V	100	42.6	●	●		●	●	●
SRT1315A	3.15A	250V	100	89.0	●	●		●	●	●
SRT1400A	4A	250V	100	95.0	●	●		●	●	●
SRT1500A	5A	250V	100	148	○		●	●	●	
SRT1630A	6.3A	250V	100	195	●		●	●		

● 表示已获认证  
 ○ 表示认证中